



UNLIMITED RECYCLING RESOURCES LLC

4195 Chino Hills Parkway #472
Chino Hills, CA 91709

GB-1111F-2512

Model Specifications	120 HP	10" Cylinder	114" Stroke
<ul style="list-style-type: none">• Feed opening• Bale Chamber• Bale Size expandable• Bale Weight• Tension Cylinder• Ram Rollers• Machine Weight• Main Baler Body Frame• Cutting Knife Replaceable• Auto Tier• Number of Ties• Wire Arrangement• Ram Face Pressure• Tension Force• Tension Type• Cycle Time (No Load)• Cycles Per Minute• Tie Cycle• Production (O.C.C.)			94" x 40" 43" x 30" x 114" 43" x 43" x 59" (Adjustable) Up to 2,800 lbs. 10" Diameter 10" Stroke 12 52,900 lbs. SS41 Tool Steel Scatter Cutter Hydraulic Actuated Inserter 5 50, 100 spools or 1,000 stand 140 PSI 470 tons 4-Way Free Floating Clamber 9.6 Sec. 6.2 20– 26 Sec. 22 - 29 TPH

Hydraulic System

<ul style="list-style-type: none">• Hydraulic System• Oil Reservoir• Hydraulic cooling• Hydraulic filtration• Hydraulic Pump Brand• Valve Brand	Regenerative 713 Gallons 2700 Liters Air Cooling Suction Filter DENISON VICKERS
--	--

Electrical System (UL)

- PLC MITSUBISHI
- Operator Interface Human Machine Interface
- Main Motor Control STAR/DELTA
- Controller Brand SIEMENS
- UL Standard

After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: steel wire (2.7mmDIA) annealed twice, cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.