

GB-0505F-1202

Model Specifications	20 HP	5" Cylinder	35" Stroke
 Feed opening Bale Chamber Bale Size expandable Bale Weight (O.C.C.) Machine Weight Main Baler Body Fra Cutting Knife Replace Auto Tier Number of Ties Wire Arrangement Ram Face Pressure Cycle Time (no load) Production (O.C.C.) 	me eable		25" x 18" 20" x 20" x 35" 20" x 20" x 24" up to 150 lbs. 7,750 SS41 Tool Steel Scatter Cutter Hydraulic Actuated Inserter 3 50, 100 lb. spools 120 PSI 6.4 Sec. 1.7 – 2.2 TPH
Hydraulic System			
 Hydraulic System Oil Reservoir Hydraulic cooling Hydraulic filtration Hydraulic Pump Brar 	nd		Regenerative 132 Gallons 500 Liters Air Cooling Suction Filter DENISON

• Valve Brand

Electrical System (UL)

- PLC
- Operator Interface
- Main Motor Control
- Controller Brand

MITSUBISHI Human Machine Interface STAR/DELTA Scheider

VICKERS

• UL Standard

After Service System

• Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: High tensile galvanized baling wire (3.1 mm DIA), cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.