



# GB-7575TR-2004

Model Specifications	40 HP	8" Cylinder
• Feed opening		47" x 30"
• Bale Chamber		30" x 30" x 104"
• Bale Size		30" x 30" x 40"
• Compressing Cylinder		8" Diameter
• Push-Out Cylinder		6" Diameter
• Machine Weight		26,500 lbs.
• Main Baler Body Frame		SS41/HARDOX 500/S50C
• Cutting Knife Replaceable		Tool Steel Scatter Cutter
• Auto Tier		Accent or L&P
• Cycle Time (No Load)		15.3 Sec.
• Cycles Per Minute		3.9
• Production (O.C.C.)		3.5-5 TPH

## Hydraulic System

• Hydraulic System	Regenerative
• Hydraulic cooling	Air Cooling
• Hydraulic filtration	Suction Filter
• Hydraulic Pump Brand	DENISON
• Valve Brand	VICKERS

## Electrical System (UL)

• PLC	MITSUBISHI
• Operator Interface	Human Machine Interface
• Main Motor Control	Reduced Amperage Starting
• Controller Brand	Scheider
• UL Standard	

## After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

## Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: High tensile galvanized baling wire (3.1 mm DIA), cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.