



UNLIMITED RECYCLING RESOURCES LLC

4195 Chino Hills Parkway #472
Chino Hills, CA 91709

GB-1108FSS-2004

Model Specifications	40 HP	8" Cylinder	79" Stroke
<ul style="list-style-type: none">• Feed opening• Bale Chamber• Bale Size expandable• Bale Weight• Tension Cylinder• Ram Rollers• Machine Weight• Main Baler Body Frame• Cutting Knife Replaceable• Auto Tier• Number of Ties• Wire Arrangement• Ram Face Pressure• Tension Force• Tension Type• Cycle Time (No Load)• Cycles Per Minute• Tie Cycle• Production (O.C.C.)			63" x 40" 43" x 30" x 79" 43" x 30" x 60" (Adjustable) Up to 1,275 lbs. 8" Diameter 8" Stroke 12 27,300 lbs. SS41 Tool Steel Scatter Cutter Hydraulic Actuated Inserter 4 Positions up to 8 Wires 50, 100 spools or 1,000 stand 128 PSI 300 tons 4-Way Free Floating Clamber 24.2 Sec. 2.4 35 – 39 Sec. 5.8 – 7.6 TPH

Hydraulic System

<ul style="list-style-type: none">• Hydraulic System• Oil Reservoir• Hydraulic cooling• Hydraulic filtration• Hydraulic Pump Brand• Valve Brand	Regenerative 360 Gallons 1360 Liters Air Cooling Suction Filter DENISON VICKERS
--	--

Electrical System (UL)

- PLC
- Operator Interface
- Main Motor Control
- Controller Brand
- UL Standard

MITSUBISHI
Human Machine Interface
STAR/DELTA
SIEMENS

After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: steel wire (2.7mmDIA) annealed twice, cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.